

# FIFISH W6 NAVI

## Technical Specifications



### ROV

Dimensions	710mm(l) x 490mm(w) x 339mm(h)
Weight	23.4kg
Depth Rating	350m
Payload	10kg
Speed	>3 Knots (>1.5m/s)
Propellers	6 Degrees of Freedom
	Movement: left & right, up & down, forward & backward, 360° yaw, 360° pitch, 360° roll
	Hard Anodized Aluminum Alloy
Operating Temp.	-10 °C ~ 60 °C (Operational Temp. Range)
Battery	1-4h (Dependent on Work Environment)
	388.8Wh Capacity
	Quick Charging: Full Power in 1.5h (Actual Charging Speed May Differ)
Navigation	Underwater Inertial Navigation System (U-INS)

### Sensors

Downward DVL	Detection range: 0.1m-100m	Station Lock & Collision Avoidance
Gyroscope	±0.1°	Posture Lock: ± 0.1° pitch angle or ± 0.1° roll angle, moving in any direction
Accelerometer	±0.1°	
Magnetometer	±1°	
Depth Sensor	Suspension within ±1 cm	Depth Lock
Temp. Sensor	±1°	
Laser Scaler	Wavelength: 660nm (Red)	Smart Measurement
	Type: Dual Spot Laser	
	Distance: 10cm Apart	

### Lighting

Brightness	6000 Lumen LED * 2
CCT	5500K
Beam Angle	120°
Brightness Levels	3

### Camera

Quantity	Dual 4K Camera System
Aperture	Aperture: f/1.8
Field of View	Vertical (Underwater): 52°
	Horizontal (Underwater): 87°
	Diagonal (Underwater): 96°
Focus Range	0.3m~ + ∞
Sensor	1/1.8" CMOS
Pixels	12MP
Shutter Speed	5-1/5000 Second
Burst Shooting	1/3/5/10 Frames
ISO	100-6400 (Auto/Manual)
White Balance	2800-9000K (for Seawater & Freshwater, Auto/Manual)
Exposure Compensation	-3.0 EV to +3.0 EV (Auto/Manual)
Photo Resolution	4:3 = 4000 × 3000
	16:9 = 3840 × 2160
Photo Format	JPEG, DNG
Video Resolution	4K UHD: 25/30 fps
	1080p FHD: 25/30/50/60/75/90 fps
	720P HD: 25/30/50/60/75/90 fps
Video Encode	H.264
Video Format	MP4
Stabilization	Electronic Stabilization (EIS)
Color System	NTSC & PAL
Internal Storage	External TF Card (FAT32 File System, Up to 256GB Maximum Capacity)
AI Vision Functionality	Vision Lock, Auto Navigation

Please contact the QYSEA team for more details; specifications are subjected to change without notice.

# FIFISH W6 NAVI

## Technical Specifications



### Charger

ROV	Input: 100-240V, 50/60 Hz, 3A MAX Output: 25.2V – 6A * 2
Controller	Input: 100-240V, 50/60 Hz, 0.5A MAX Output: 5V – 3A

### Port Interface

Quantity	4
Material	Stainless steel 316
Interface	24V @ 5A ETHERNET, UART
Adjustable Power	Adaptive Voltage Range for External Add-on Accessories
Secure Plug	Self-diagnostic Tests & Leakage Prevention

### Robotic Arm

Max. Grip Strength	20kgf
Supply Voltage	10V-26V
Maximum Current	3A
Max. Grip Size	125mm

### Controller

Wireless Network	5GHz WiFi: 802.11a/n/ac
Usage Time	Up to 4 hours
File Download Format	MicroSD Card: FAT32 & EXFAT (128GB Max. Storage Support)
HDMI Output	HDMI Box Required

### Tether & Spool

Cable length	305m
Tensile strength	200kgf
Cable diameter	6mm
Tether Weight (Underwater)	Neutral Buoyancy

### Q-DVL

Dimensions	130mm(l) x 154mm(w) x 34.5mm(h)
Weight	840g in Air, 550g in Water
Velocity Resolution	0.1 mm/s
Communication	100-BaseT Ethernet & Serial (UART 921600 Baud)
Min. Altitude	10cm
Max. Altitude	100m

Please contact the QYSEA team for more details; specifications are subjected to change without notice.